



## PL-PULSE programmable pulse output



### General description

The pulse output module is intended for transmission of synchronisation pulses. The module has one output that can transmit sync. pulses type PPS, PPM or PPH transmitted in one of the following formats.

- a. TTL pulses
- b. 24 V DC pulses

On the front plate there are 2 LED indications for pulse control.

The pulse length and interval is programmable

### Technical data's:

Art.No.:	123734-00
Microprocessor:	Hitachi H8S/2394
Pulse length selectable:	0.01 – 32 seconds.
Pulse interval selectable:	Second/ minute / hour
Output connection and signal level	
BNC female connector:	TTL levels into 50 Ohm. The rising edge on time.
2-polar screw terminal:	24VDC
Timing accuracy:	
Locked to GPS	<10us to UTC
Ambient temperature:	0°C up to +40°C
Measurements:	Width = 20,0 mm. (4TE), Height = 128,4 mm, Depth = 160 mm.
Weight:	0.15 kgs

We reserve the right to changes at any time.

WESTERSTRAND URFABRIK AB Sweden

P.O. Box 133, SE- 545 23 TÖREBODA  
E-mail: info@westerstrand.se

Tel +46 506-480 00 Fax +46 506-480 51  
Internet: www.westerstrand.se