



Stand-alone Clocks

Analogue Clocks type QUARTZ



Westerstrand analogue clocks type **QUARTZ** have a built-in **high accuracy quartz crystal as time base.**

In/Outdoor with aluminium housing

- Operation: Battery or mains 230VAC
Sizes: dia. 400, 600 and 900 mm.
Housing: Aluminium in dark grey (RAL 7037). Illumination, with or without internal LED-Illumination.
Dial face: Mat white with either black numerals 1-12 or hour marks.
Hands: Black hours- and minutes hands.
Protection: Convex protection of acrylic plastic.
Single sided: For surface wall mounting.
Double sided: Including bracket for either wall mounting, standing on roof or hanging from ceiling.

Battery operated - in/outdoor.

The movement can work with two types of batteries. Alkaline batteries, art.No. 113190-00 (for indoor use), and lithium batteries for indoor/outdoor use, purchased locally (cannot be ordered by Westerstrand). Lifetime of the batteries in separate description.

Mains 230VAC operated - in/outdoor.

During a power failure the clock is temporarily stopped. With the option running reserve (113195-00), the clock will continue to work during the power failure for 12 hours.

External setting device

Mains 230VAC operated Quartz Clocks can as option be delivered with external setting device (113198-00).

| Operation | In/Outdoor | Single/ double sided | Size mm. | Type of dial face A = numerals 1-12 H = hour marks | Art.No. | Internal illumination |
|--------------|------------|----------------------------|-------------|--|--------------|--------------------------|
| Battery | Indoor | single sided | 400 | A | 10 41 720-00 | No |
| Battery | Indoor | single sided | 400 | H | 10 43 720-00 | No |
| Battery | Indoor | single sided | 600 | A | 10 61 720-00 | No |
| Battery | Indoor | single sided | 600 | H | 10 63 720-00 | No |
| Battery | Indoor | single sided | 900 | A | 10 91 720-00 | No |
| Battery | Indoor | single sided | 900 | H | 10 93 720-00 | No |
| Battery | Outdoor | single sided | 400 | A | 11 41 720-00 | No |
| Battery | Outdoor | single sided | 400 | H | 11 43 720-00 | No |
| Battery | Outdoor | single sided | 600 | A | 11 61 720-00 | No |
| Battery | Outdoor | single sided | 600 | H | 11 63 720-00 | No |
| Battery | Outdoor | single sided | 900 | A | 11 91 720-00 | No |
| Battery | Outdoor | single sided | 900 | H | 11 93 720-00 | No |
| Battery | Outdoor | single sided | 600 | A | 11 62 720-50 | Yes |
| Battery | Outdoor | single sided | 600 | H | 11 64 720-50 | Yes |
| Battery | Outdoor | single sided | 900 | A | 11 92 720-50 | Yes |
| Battery | Outdoor | single sided | 900 | H | 11 94 720-50 | Yes |
| Battery | Outdoor | double sided ¹⁾ | 400 | A | 14 41 720-00 | No |
| Battery | Outdoor | double sided ¹⁾ | 400 | H | 14 43 720-00 | No |
| Battery | Outdoor | double sided ¹⁾ | 600 | A | 14 61 720-00 | No |
| Battery | Outdoor | double sided ¹⁾ | 600 | H | 14 63 720-00 | No |
| Battery | Outdoor | double sided ¹⁾ | 900 | A | 14 91 720-00 | No |
| Battery | Outdoor | double sided ¹⁾ | 900 | H | 14 93 720-00 | No |
| Battery | Outdoor | double sided ¹⁾ | 400 | A | 14 42 720-50 | Yes |
| Battery | Outdoor | double sided ¹⁾ | 400 | H | 14 42 720-50 | Yes |
| Battery | Outdoor | double sided ¹⁾ | 600 | A | 14 62 720-50 | Yes |
| Battery | Outdoor | double sided ¹⁾ | 600 | H | 14 64 720-50 | Yes |
| Battery | Outdoor | double sided ¹⁾ | 900 | A | 14 92 720-50 | Yes |
| Battery | Outdoor | double sided ¹⁾ | 900 | H | 14 94 720-50 | Yes |
| Mains 230VAC | Outdoor | single sided | 400 | A | 11 41 700-00 | No |
| Mains 230VAC | Outdoor | single sided | 400 | H | 11 43 700-00 | No |
| Mains 230VAC | Outdoor | single sided | 600 | A | 11 61 700-00 | No |
| Mains 230VAC | Outdoor | single sided | 600 | H | 11 63 700-00 | No |
| Mains 230VAC | Outdoor | single sided | 900 | A | 11 91 700-00 | No |
| Mains 230VAC | Outdoor | single sided | 900 | H | 11 93 700-00 | No |
| Mains 230VAC | Outdoor | single sided | 600 | A | 11 62 700-50 | Yes |
| Mains 230VAC | Outdoor | single sided | 600 | H | 11 64 700-50 | Yes |
| Mains 230VAC | Outdoor | single sided | 900 | A | 11 92 700-50 | Yes |
| Mains 230VAC | Outdoor | single sided | 900 | H | 11 94 700-50 | Yes |
| Mains 230VAC | Outdoor | double sided ¹⁾ | 400 | A | 14 41 700-00 | No |
| Mains 230VAC | Outdoor | double sided ¹⁾ | 400 | H | 14 43 700-00 | No |
| Mains 230VAC | Outdoor | double sided ¹⁾ | 600 | A | 14 61 700-00 | No |
| Mains 230VAC | Outdoor | double sided ¹⁾ | 600 | H | 14 63 700-00 | No |
| Mains 230VAC | Outdoor | double sided ¹⁾ | 900 | A | 14 91 700-00 | No |
| Mains 230VAC | Outdoor | double sided ¹⁾ | 900 | H | 14 93 700-00 | No |
| Mains 230VAC | Outdoor | double sided ¹⁾ | 400 | A | 14 42 700-50 | Yes |
| Mains 230VAC | Outdoor | double sided ¹⁾ | 400 | H | 14 44 700-50 | Yes |
| Mains 230VAC | Outdoor | double sided ¹⁾ | 600 | A | 14 62 700-50 | Yes |
| Mains 230VAC | Outdoor | double sided ¹⁾ | 600 | H | 14 64 700-50 | Yes |
| Mains 230VAC | Outdoor | double sided ¹⁾ | 900 | A | 14 92 700-50 | Yes |
| Mains 230VAC | Outdoor | double sided ¹⁾ | 900 | H | 14 94 700-50 | Yes |

¹⁾ = including bracket for either wall mounting, standing on roof or hanging from ceiling