



## Westerstrand LED Digital Clocks

# Time/Temperature LED 15-19-25-30-45



**T/T-LED 15-19-25-30-45** for outdoor use.  
Alternate between time (hours and minutes) and temperature.

## TIME/TEMPERATURE

- Alternate between time, temperature and date (via set up function)
- Digits of red diodes
- The light intensity of the digits is adjustable by a dimmer control
- 48 hours memory backup. After a mains failure correct time is automatically displayed
- Including Air-temperature sensor with 5m cable
- Automatic summer/winter time change
- Easy to use – via three buttons or radio controlled remote

### Operation method:

24VDC polar reversing imp. 1/1- alt 1/2-min. or Time Code from Master Clock or as a stand-alone unit. Can as option be controlled via Radio/Satellite receiver

### Mounting/Installation:

Via bracket, standing, hanging or surface wall

### Options:

122980-51 Satellite receiver GPS



### Technical data:

Housing:	Aluminium housing painted with black polyester powder
Front:	Non-reflective polycarbonate, Impact resistance 190J
Supply voltage:	Mains 230V 50Hz AC
Power consumption:	Impulse 5 mA
Protection class:	Similar to IP54
Standards:	EN61000-6-3:2001 EN61000-6-2:2005
Accuracy time:	± 1 sec/24 h
Accuracy temp:	± 1 °C
Interval time/temp:	Selectable 1-19 sec

Avilable sizes / dim		
Art	Digits	Dim (WxHxD)
T/T LED 15	150mm	685x245x92mm
T/T LED 19	190mm	740x270x92mm
T/T LED 25	250mm	900x330x92mm
T/T LED 30	300mm	1000x380x92mm
T/T LED 45	450mm	1510x600x110mm

We reserve the right to changes at any time.