



PACE CLOCK - for interval training



Pace Clock with stand

Single sided Pace Clock with housing of aluminium in grey RAL 7037 for surface wall mounting, stand as option.

Mat white dial face with black numerals and marks with convex protection glass of polycarbonate.

Available in two models:

- with seconds hand shaped like a propeller, i.e. four blades in green, red, blue and yellow.
- with black seconds hand

The Delivery includes:

1 off Transformer 230VAC/24VAC

1 off 3 metre connection cable (between clock and transformer)

1 off 1,5 metre connection cable with plug (transformer to mains supply)

Art.No.	Size exterior measurements	Type of seconds hand	Weight
114085-20	∅ 600 mm.	Propeller - 4 hands	5,0 kgs.
114085-21	∅ 600 mm.	1 black hand	5,0 kgs.
114083-20	∅ 900 mm.	Propeller - 4 hands	10,0 kgs.
114083-21	∅ 900 mm.	1 black hand	10,0 kgs.

Technical Data – Pace Clock

Connection voltage: 230V 50Hz via transformer 230V/24V 50-60 Hz
 Operating voltage: 24V AC
 Internal power consumption: 180mA
 Ambient temperature: 0°C up to +40°C
 Relative humidity: 85%
 Protection class: IP52

Technical Data – Transformer

Connection voltage: 230V 50Hz
 Operating voltage: 24V AC
 Ambient temperature: 0°C up to +40°C
 Relative humidity: 85%
 Protection class: IP44
 Dimension (LxWxD): 140x80x70mm
 Weight: 0,9 Kgs

We reserve the right to make changes at any time.