WESTERSTRAND SPORTS SYSTEMS Section Multi-purpose Scoreboards – LED

<u>DESCRIPTION – BASIC LED250 MULTISPORT</u> <u>ART NO 117621-02</u>

Basic module is a single sided Scoreboard for indoor sports The delivery includes:

1 pc. Multi-purpose scoreboard with built in siren (indoor use)

1 pc. Wall mounting kit according to description 2582

1 pc. Instruction 2570

1 pc Hard wired remote

SPORTS: HANDBALL - BASKETBALL - VOLLEYBALL - FUTSAL - FLOOR BALL -

TENNIS - TABLE TENNIS - BADMINTON - INDOOR FOOTBALL - BOXING - WRESTLING

WEIGHTLIFTING - WATERPOLO - TIME KEEPING - GENERAL USE



The design makes it suitable for most indoor sports and can also be combined with various add-on modules e.g. Shot Timers for 24-seconds rule in basketball, Penalty units, Individual foul units It is controlled from our self-instructing remote control unit with pre-programmed rules adapting the control unit to each individual sport.

The included remote control unit is hard wired, connection to Scoreboard acc to diagram on page 4.

Match/Game time Minutes and seconds, four digits, count-up or down

Local day time can be indicated when no game is being played

Game in progress/stopped Indicated by green/red dot.

Score indication 000-999 (three digits per team) for Basketball and Futsal

and 00-99 (two digits per team) for other sports

Period 1-9

Penalty 1 penalty time/team

Serve/ball possession Indicated with arrows

Foul 1 digit/team for team foul and for basketball these digits also indicate last

individual foul and player No (blinking)

Time-out Count-down of time is indicated instead of match/game time (not in basketball),

and by dots

Siren Built-in.

Sounds automatically at finished game, time-out and break pause.

By manually pressing a key, the siren can also sound at any requested time

Maintenance The electronic can easily be removed by loosen two screws in the bottom of the

scoreboard.


More detailed description of the function for each individual sports available on separate data sheets. We reserve the right to make changes at any time.




WESTERSTRAND Sweden

WESTERSTRAND

MOUNTING





TECHNICAL DATA:

Case: Aluminium, black
Front: Polycarbonate, 3mm

Digits: LED's (SMD)

Digit height: 250 mm (score, time, penalty and teamfoul), 190mm (period)

Colour of digits: Red / Green / Yellow

Colour of fixed text: Yellow
Size of dots: Ø 45mm

Colour of dots: 2 yellow and 1 red / team

1 green and 1 red for indication game in progress/stopped

Exterior dimensions of case: (WxHxD) 2000 x 1250 x 50 mm

Weight: 30 kgs

Reading distance: Approx. 120 metres

Connection voltage: 230V 50-60 Hz AC

Power supply and electronics: The electronic can easily be removed by loosen two screws in

the bottom of the scoreboard.

Power consumption: Max. 160 VA

Ambient temperature: $\pm 0^{\circ}$ C up to $\pm 40^{\circ}$ C

Siren: Built in, 105 dB

DESCRIPTION: REMOTE CONTROL UNIT BASIC 117600-05

The TFT display shows the same information as the Scoreboard. Easy to use through pre-programmed international rules.

Remote control Art.No. 117600-05 for hardwired operation of Scoreboards


The delivery includes:


1 pc. 22497-00 Remote control unit with pre-programmed sports

1 pc. 40536-42 Connection box



- 1. TFT display (800 x 480 pixels)
- 2. Function keys
- 3. Numeric keys
- 4. D-sub connector
- 5. USB connector
- 6. Connector for 24-seconds control handle
- 7. Connector for start/stop handle





TECHNICAL DATA:

Exterior measurements: (WxHxD) 295 x 195 x 50 mm.

Weight: 1,2 kgs

Ambient temperature: $\pm 0^{\circ}$ C up to $\pm 40^{\circ}$ C.

Colour Black casing with blue overlay

Case: Aluminium

Connection to basic module: See block diagram on next page.3,0 metre cable with 5-polar audio connection box are included in the shipment.

OPTION – see separate data sheets

- Start/Stop handle:
- Siren for medium and large halls
- Audio output for siren
- RS 232 output
- Red/green referee lamps
- 114915-00 Bag for storage of remote


WESTERSTRAND URFABRIK AB Sweden

P.O. Box 133, SE-545 23 TÖREBODA Tel. +46 506-48 E-mail: info@westerstrand.se Internet: www.v

Tel. +46 506-480 00 Fax +46 506-48051 Internet: www.westerstrand.se

CABLE DIAGRAM





A: The module has a power cord that must be connected to an earthed power outlet with a 10A fuse.

* This cable is supplied in the delivery

cable length m	А	В	D	E	*
< 50	Power cord	4 x 0,5			RJ12
< 100		4 x 1,0			
< 150		4 x 1,5			
< 250		4 x 2,5	Cat 5/6	Cat 5/6	
connect. diagr.		086363-03	085170-09	2723	2723
remark		Shielded	UTP	UTP	

We reserve the right to make changes at any time.